Attorney Docket No.: Q67887

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application:

LISTING OF CLAIMS:

- 1. (Previously Presented) An organic electroluminescent (EL) display, comprising:
 a plurality of ITO films which are disposed on a transparent substrate via an inter-layer insulating film;
 - a first insulating film which is disposed between adjacent ones of said ITO films; an organic EL thin film deposited on said ITO films; a cathode thin film deposited on said ITO films; and
- a plurality of insulative mask supporting layers constituting a part of or a whole of said first insulating film, said mask supporting layers preventing a metal mask which is used in formation of said organic EL thin film and said cathode thin film, from being in contact with a pixel portion of said transparent substrate.
- 2. (Original) The organic EL display according to claim 1, wherein said display uses a TFT substrate in which said ITO films and TFT layers that are disposed via said interlayer insulating film are connected to one another in an active matrix system.
- 3. (Original) The organic EL display according to claim 1, wherein said mask supporting layers are formed by one of a resist, ceramics and an organic resin.

- Attorney Docket No.: Q67887
- 4. (Original) The organic EL display according to claim 1, wherein said insulative mask supporting layers having a reverse tapered shape are disposed on said insulating film.
- 5. (Withdrawn) A method of producing an organic EL display, said method comprising the steps of:

disposing a plurality of ITO films on a transparent substrate via an inter-layer insulating film;

disposing a plurality of mask supporting layers on said inter-layer insulating film;
overlaying a metal mask of a predetermined pattern having openings therein on said
transparent substrate so as to support said metal mask by said mask supporting layers; and
depositing an organic EL thin film and a cathode thin film on said ITO films through the
openings of said metal mask.

6. (Withdrawn) The method of producing an organic EL display according to claim 5, further comprising the steps of: disposing said ITO films and TFT layers on said transparent substrate via said inter-layer insulating film:

connecting said ITO films and said TFT layers to one another in an active matrix system; and

then forming said mask supporting layer.

7. (Previously Presented): An organic electroluminescent (EL) display, comprising: a plurality of ITO films which are disposed on a transparent substrate via an inter-layer

Attorney Docket No.: Q67887

insulating film;

a first insulating film which is disposed between adjacent ones of said ITO films;

an organic EL thin film deposited on said ITO films;

a cathode thin film deposited on said ITO films; and

a plurality of insulative mask supporting layers disposed on at least a part of said first

insulating film, said mask supporting layers preventing a metal mask which is used in formation

of said organic EL thin film and said cathode thin film, from being in contact with a pixel portion

of said transparent substrate.

8. (Previously Presented) The organic EL display according to claim 7, wherein said

insulative mask supporting-layers are formed from said first insulating layer.

9. (Previously Presented) The organic EL display according to claim 7, wherein said

insulative mask supporting layers are formed on said first insulating layer.

10. (Previously Presented) The organic EL display according to claim 7, wherein said

insulative mask supporting layers are stripe-shaped.

11. (Previously Presented) The organic EL display according to claim 7, wherein said

insulative mask supporting layers are island-shaped.

12. (Cancelled)

- Attorney Docket No.: Q67887
- 13. (Previously Presented) The organic EL display according to claim 7, wherein said insulative mask supporting layers have a thickness of at least 2 µm.
- 14. (Previously Presented) The organic EL display according to claim 7, wherein said insulative mask supporting layers have at least one portion which is either taper-shaped or ridge-shaped.
- 15. (Previously Presented) The organic EL display according to claim 8, wherein said insulative mask supporting layers are constituted by locally thickened portions of said first insulating layer.
- 16. (Previously Presented) The organic EL display according to claim 9, wherein said insulative mask supporting layers are formed directly on said first insulating layer.
- 17. (Previously Presented) The organic EL display according to claim 7, wherein said insulative mask supporting layers is disposed such that a predetermined gap is maintained between a corresponding one of said ITO films and said metal mask.